

TABLE AND CHAIRS HOW-TO:


SUPPLY

- □ Kilz Complete Coat™ Paint and Primer
- □ 100-150 Grit Sandpaper
- □ Painter's Tape
- ☐ Paint Brush

- □ Measuring Tape
- □ Chairs
- □ Table
- □ 3/8"-1/2" Synthetic Roller



PROTIP: For glossy surfaces, scuff sand with the appropriate sandpaper prior to coating.



PROTIP: Measure peak to peak, as well as the distance between the points along the side of the table.



PRO TIP: Use a high quality synthetic brush or 3/8"-1/2" synthetic roller for the application. When painting a horizontal surface, like a tabletop, apply thin coats.



- For best results start with a properly prepared and previously painted or primed surfaces. Remove any loose or peeling paint and wash off dirt or grease with a non-soapy detergent or a TSP substitute. Rinse well and allow surface to dry.
- Tape off areas to be painted. To achieve a geometric pattern we recommend using measuring tape to evenly space tape.
- 3 Stir paint before and during application to make sure it is mixed.
- Remove the painters tape when the paint is wet, or have a razor to cut the film if you've let the paint dry.
- Allow to dry. The product dries to touch in 2 hours (at 77° F and 50% relative humidity) or longer in cooler temperatures and/or higher humidity.