



INTERIOR MULTI-SURFACE PRIMER & SEALER

NO. 52000



PRODUCT INFORMATION

KILZ® HIDE-ALL® Primer is a high hiding, fast drying, multi-surface water-based primer-sealer formulated to minimize problems caused by dark colors, minor surface marks, textures and porosity differences. Ready to brush, roll or spray, it can be topcoated after one hour with water-based or oil-based paint. Use KILZ HIDE-ALL Primer on interior surfaces including drywall, cured plaster, woodwork, masonry, concrete block, brick and previously painted surfaces. Not for use over glossy surfaces or on floors.

RECOMMENDED USES:

Use on properly prepared interior surfaces, such as:

- Wood
- Plaster
- Brick
- Drywall
- Masonry
- Previously Painted Surfaces[†]

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

White

No. 5200 128 oz / 2 oz

Note: Tinting to a lighter shade than the topcoat is recommended. Tinting may not be available for 2 gallon size pails.

SHEEN: 85°=<10

Sheen levels depend on porosity and various surface irregularities.

COMPOSITION

Vehicle: PVA/Acrylic

Weight Solids: 43.6% (+/-) 2%

Volume Solids: 31.3% (+/-) 2%

Weight / Gallon (lbs): 10.55 (+/-) 0.2 lbs./gal

Viscosity: 101 - 109 KU

VOC: 25 g/L

The addition of colorants may add VOCs.

Flashpoint: N/A

Recommended Film Thickness:

Wet: 5.3 mils / Dry: 1.7 mils @ 300 Sq. Ft./Gal.

Wet: 4.0 mils / Dry: 1.2 mils @ 400 Sq. Ft./Gal.

Coverage Rate: Coverage: 300 - 400 sq. ft. per gallon, depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

PREMIUM APPLICATION TOOLS:

Airless Spray:

Fluid pressure of 1,800 - 3,000 psi

Tip: .017" - .021"

Filter: 60 mesh

Brush: Nylon / Polyester Blend

Roller: Smooth Surfaces: 3/8" - 1/2" nap

Porous Surfaces: 1/2" - 3/4" nap

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew, loose peeling paint, rust and all other foreign substances.

If washing is necessary, use a non-soapy detergent or a TSP substitute, rinse well and allow to dry.

Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.*

Glossy Surfaces: Not Recommended. Use products such as KILZ® ADHESION, KILZ® RESTORATION or KILZ® PREMIUM Primers over properly prepared glossy surfaces.

Mold or Mildew Covered Surfaces: Wash the area with mildew remover, rinse with water and allow to dry before priming. Use a product such as KILZ® PREMIUM, KILZ 2® or KILZ® KITCHEN & BATH Primers on mildew-prone surfaces.

Masonry, Brick, Stucco and Plaster: KILZ HIDE-ALL Primer may be used on clean, dry, aged interior masonry surfaces that have cured (dried) at least 30 days.

APPLICATION:

- Eye protection is recommended.
- Only apply if surface, air and product temperatures are between 50°-90°F (10°-32°C).
- Apply using a brush, roller or sprayer.
- DO NOT THIN. Product is formulated for use at package consistency. For spray applications, a small amount of water (no more than ½ pint per gallon) may be added.
- Stir thoroughly before and occasionally during use.
- Stains: KILZ HIDE-ALL Primer is formulated to hide minor, non-bleeding scuffs and stains before topcoating; for heavier stains use a product such as oil-based primers such as KILZ® ORIGINAL Primer or water-based primers such as KILZ® RESTORATION Primer.

COMPLIES WITH THE BELOW AS OF 01/01/19			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	LEED®	NO

*Product may help projects qualify for LEED credits. Please see www.usgbc.org/LEED for additional details.

- Tinting: May be tinted with up to 2 oz. (60 mL) of universal colorant per gallon. Tinting to a lighter shade than the topcoat is recommended. Tinting may not be available for 2 gallon size pails.

DRY TIME at 77°F (25°C), 50% RH

- Dries to touch in 30 minutes.
- Recoat after 1 hour.
- Lower temperatures, higher humidity, poor ventilation or heavy application can significantly increase dry and recoat times.

CLEAN-UP & DISPOSAL:

- Clean equipment and paint spatters with warm, soapy water.
- If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations.
- Do not dispose of this product down a drain. Please consider donating any unused product.
- For recycling or disposal information contact your local household refuse collection service.

CAUTIONS/LIMITATIONS:

- **IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS**
- **KEEP FROM FREEZING**
- **DO NOT USE ON FLOORS**
- **DO NOT USE WHEN AIR AND SURFACE TEMPERATURES ARE BELOW 50°F OR ABOVE 90°F (10-32°C)**
- **SHELF LIFE UNDER NORMAL CONDITIONS IS TWO YEARS UNOPENED**

KILZ®
HIDE-ALL®

INTERIOR MULTI-SURFACE PRIMER & SEALER

NO. 52000



GENERAL INFORMATION:

WARNING

Cancer and Reproductive Harm— www.P65Warnings.ca.gov

***WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects, or other reproductive harm.

***WARNING:** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

CAUTION! IRRITANT! HARMFUL OR FATAL IF SWALLOWED. AVOID CONTACT WITH EYES. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID BREATHING OF DUST, VAPORS OR SPRAY MIST. USE ONLY WITH ADEQUATE VENTILATION. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/ mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH / MSHA TC -23C or equivalent) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling and before smoking or eating.

FIRST AID: If swallowed, do not induce vomiting. Get medical attention. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.

CAUTION: KEEP OUT OF REACH OF CHILDREN

DO NOT TAKE INTERNALLY