

GRAY



KILZ 2 LATEX GRAY PRIMER

NO. 2294



PRODUCT INFORMATION

KILZ 2® Latex Gray Primer is a fast drying, water-based, multi-surface primer-sealer-stainblocker which is specifically designed for use under dark, rich and deep vibrant color topcoats. This helps achieve more accurate color with fewer coats of paint and by improving the hiding of previous colors. KILZ 2 Gray Primer has excellent adhesion, sealing properties and a very mild odor. Effectively blocks “medium” stains including water stains, rust, grease, ink, pencil and felt marker. Use on interior and exterior surfaces. Use under or over latex or oil-based paints. Not recommended on flooring.

RECOMMENDED USES:

Use on properly prepared interior and exterior surfaces such as:

- Drywall
- Plaster
- Paneling
- Wood
- Brick
- Masonry
- Stucco
- Painted Metal

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. 2294 128 oz. / 2 oz.

Resin Type: Acrylic Polymer

Sheen: < 10.0 @ 85°

Sheen levels depend on porosity and various surface irregularities.

Weight per Gallon: 10.63 lbs.

% Solids by Volume: 33.64%

% Solids by Weight: 47.35%

VOC: <50 g/L

Flash Point: N/A

Viscosity: 95 - 104 KU

Recommended Film Thickness:

Wet: 5.3 mils / Dry: 1.8 mils @ 300 Sq. Ft./Gal.

Wet: 4.0 mils / Dry: 1.4 mils @ 400 Sq. Ft./Gal.

Coverage: 300 - 400 Sq. Ft./Gal. depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon / Polyester

Roller: 3/8" - 3/4" nap

Airless Spray: Fluid pressure of 2,500 - 3,200 psi

Tip: .015" - .021"

Filter: 60 mesh

Thinning: Not recommended. Product is formulated for use at package consistency only.

Dry Time: @ 77°F, 50% RH

Longer dry time required in cooler temperatures and in higher humidity.

To Touch: 30 minutes

To Recoat: 1 hour

SURFACE PREPARATION:

The surface must be clean, free of dust, grease, wax, peeling paint, mold, mildew and wallpaper paste. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.

Unpainted, exterior wood: Exposed to sun and/or moisture longer than 2-4 weeks must be cleaned and sanded before priming.

Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.

Masonry, Brick, Stucco and Plaster: KILZ 2 GRAY Primer Interior & Exterior Water-Base Primer may be used on clean, dry, aged masonry surfaces. New masonry must be allowed to cure (dry) at least 30 days before applying KILZ 2 GRAY Primer.

Fire Restoration: It is critical to clean smoke damaged surfaces thoroughly before priming.

Primary Recommendations: Use a product such as KILZ MAX®, KILZ COMPLETE®, KILZ ODORLESS® or KILZ® ORIGINAL Primers.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit www.epa.gov/lead.

TEST SPECIFICATIONS:

Flexibility

ASTM D522 - Pass

Biological Growth

ASTM D3274 - Pass

COMPLIES WITH THE BELOW AS OF 2/1/2015			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	LEED v.3 (2009) [†]	YES

[†]Please visit www.usgbc.org/LEED for additional details. GREENGUARD is a registered trademark of UL Company.

CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun.
- Shelf life under normal conditions is two years unopened.
- Partially used cans might develop skinning if not tightly sealed.

GENERAL INFORMATION:



Warning! Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.