



## INTERIOR/EXTERIOR HIGH GLOSS PAINT

### PRODUCT INFORMATION

KILZ COMPLETE COAT™ PAINT & PRIMER IN ONE Interior/Exterior High Gloss Paint is a low VOC, low odor, premium product with excellent hide. It is highly scrubbable and easy to touch-up, resists staining, fading, and peeling. It also offers a mildew resistant finish.

### RECOMMENDED USES:

Ideal for interior walls and trim. Excellent for bedrooms, family rooms, dining rooms, kids' rooms, hallways and offices. Also great for exterior siding, trim, windows, doors and woodwork. For use over properly prepared and previously painted or primed surfaces. Apply to:

- Drywall
- Wood
- Vinyl
- Masonry
- Stucco
- Brick
- Cured Plaster
- Aluminum

NOTE: For vinyl siding, only paint with a color lighter than the original siding color.

### PRODUCT SPECIFICATIONS:

#### FILL LEVEL/ MAXIMUM TINT

##### M791 UBW/Base 1

Quart 31.5 oz. / 1oz.  
1 Gallon 126 oz. / 4oz.

#### FINISH

Sheen @ 60°: 60  
Sheen level depends on porosity of surface and various surface irregularities.

#### Resin Type: 100% ACRYLIC

- \*Weight Solids: 49%
- \*Volume Solids: 38%
- \*Weight / Gallon (lbs): 10.3
- \*Viscosity: 100-115 KU

#### VOC: < 50 g/L

The addition of colorants may add VOCs.

#### FLASHPOINT: N/A

#### COVERAGE RATE

Coverage: 300-350 sq. ft. per gallon on smooth surfaces and 200-300 sq. ft. per gallon on rough surfaces. Does not include the loss of material from spraying.

#### RECOMMENDED FILM THICKNESS

At 200 sq. ft. per gallon:

**Wet:** 8 mils; **Dry:** 3 mils

At 300 sq. ft. per gallon:

**Wet:** 5.3 mils; **Dry:** 2 mils

At 350 sq. ft. per gallon:

**Wet:** 4.6 mils; **Dry:** 1.74 mils

### APPLICATION

#### Airless Spray:

Tip: .015" - .021"  
Filter: 60 mesh  
PSI: Fluid pressure of 1,500 - 2,200

#### Roller:

Smooth Surfaces: 3/8" - 1/2" nap  
Rough Surfaces: 1/2" - 3/4" nap

#### Brush:

Nylon / Polyester Blend

**DO NOT THIN** if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a ratio of no more than 8oz. per gallon.

#### DRY TIME @ 77°F and 50% RH:

To Touch: 2 hours  
To Recoat: 4 hours  
Full Cure: 2 weeks

Darker colors may require additional dry time between coats. Cooler temperatures or higher humidity may prolong drying time.

### SURFACE PREPARATION

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

#### New Drywall:

All drywall surfaces should be sufficiently sanded smooth. Remove any remaining drywall dust prior to priming. Allow all drywall compounds to be completely dry prior to coating.

COMPLIES WITH THE BELOW AS OF 2/10/2015			
SCAQMD	YES	MPI#	NO
CARB	YES	MPI X-GREEN	NO
OTC	YES	AIM	YES
LADCO	YES		

#### Previously Painted Drywall:

Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a wiping cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

#### Glossy Surfaces:

For maximum adhesion, scuff sand the surface before coating.

#### New Wood:

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection. Remove mill glaze with sandpaper. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

#### Previously Painted Wood:

Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a tack or wiping cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

#### New Plaster:

New plaster should be thoroughly dried and cured for a minimum of 30 days before painting. When cured, clean using a mixed solution of one part vinegar and one part water to remove efflorescence and neutralize.

\*Numbers given here are from Ultra Bright White/ Base 1. This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a technical service representative, call 1-866-275-5459 (1-866-ASK-KILZ) • www.kilz.com



## INTERIOR/EXTERIOR HIGH GLOSS PAINT



### SURFACE PREPARATION *(CONTINUED)*

#### Previously Painted Plaster:

Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a tack or wiping cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

#### Stainblocking:

For unpainted or heavily stained surfaces, prime using a product such as KILZ® PREMIUM Primer/sealer/stainblocker. After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of primer and test again before top-coating the entire area. If bleeding continues, a longer dry time of the primer may be needed before top-coating.

#### Masonry:

All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth trowel concrete, create a profile using a product such as KILZ CONCRETE & MASONRY CLEANER & ETCHER No. L0502 or with mechanical means.

#### Ferrous and Non-Ferrous Metal:

The oil film on new non-ferrous metal must be removed before it is painted. Remove oil film with a detergent and water solution. For better paint adhesion, sand the surface with sandpaper, steel wool, or by using a product such as KILZ CONCRETE & MASONRY CLEANER & ETCHER No. L0502. Clean by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water.

#### Metal:

Remove all rust and mill scale using sandpaper, steel wool, abrasive blasting, or other abrading methods to create a profile on the metal's surface. New Surfaces: Clean the metal by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be primed the same day it is cleaned.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### RECOMMENDED PRIMER SYSTEMS

#### PROPERLY PREPARED NEW SURFACES:

##### Drywall, Plaster, Masonry and Wood:

- 2 coats of KILZ COMPLETE COAT™ Paint is minimum required for new or uncoated surfaces and surfaces with severe tannin and stains.

##### Ferrous & Non-Ferrous Metals:

- For previously painted metal surfaces, use KILZ PREMIUM Water Based Interior/Exterior Primer.

#### PREVIOUSLY PAINTED SURFACES:

- Use a full coat, or spot prime repaired surfaces with heavy stains, including tannin, with KILZ COMPLETE COAT Paint.

### CLEAN UP & DISPOSAL

Clean all tools and equipment with water. For disposal of empty containers and unused product, contact your household refuse collection service.

### CAUTIONS/LIMITATIONS

- IMPORTANT! Do not open can without reading instructions.
- Do not use on floors.
- Do not use when air and surface temperature are below 50°F or above 90°F.
- Shelf life under normal conditions are 2 years unopened.
- Keep from freezing.

### GENERAL INFORMATION



**WARNING:** Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**FIRST AID: If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.

\*Numbers given here are from Ultra Bright White/ Base 1.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a technical service representative, call 1-866-275-5459 (1-866-ASK-KILZ) • [www.kilz.com](http://www.kilz.com)