



INTERIOR/EXTERIOR SATIN PAINT



PRODUCT INFORMATION

KILZ SELECT LOOK™ INTERIOR/EXTERIOR SATIN PAINT is an acrylic (water-based) product. It's easy to apply, touch-up and cleans up with soap and water. It features properties such as low odor, a durable finish, and easy stain removal. It also dries quickly, resists cracking and peeling, and has a mildew-resistant film.

RECOMMENDED USES:

Use on properly prepared and primed or previously painted walls.

- **INTERIOR:** Ideal for walls, trim, windows, cabinets, woodwork and doors. Excellent for bedrooms, family rooms, dining rooms, kids' rooms, bathrooms, kitchens, and offices.
- **EXTERIOR:** Great for exterior siding, trim, windows, doors and woodwork.
- **SURFACES:** Wood, Drywall, Masonry, Stucco, Brick, Vinyl, Cured Plaster & Aluminum. Do not use on floors.

NOTE: For vinyl siding, only paint with color lighter than original siding color.

PRODUCT SPECIFICATIONS

FILL LEVEL/ MAXIMUM TINT

W3401 Ultra Bright White/ Base 1

126 oz./4 oz.

W3404 Base 2

120 oz./10 oz.

W3403 Base 3

116 oz./14 oz.

PRE-TINTED READY TO USE

W3402 White

128 oz.

W3406 Antique White

128 oz.

W3405 Country White

128 oz.

W3407 Navajo White

128 oz.

W3408 Roasted Peanut

128 oz.

W3409 Smokey Eyes

128 oz.

W3410 Platinum Ring

128 oz.

W3411 Pale Almond

128 oz.

W3412 Iced Mocha

128 oz.

W3413 Cattail

128 oz.

W3414 Red Ginseng

128 oz.

W3415 Licorice Rope

128 oz.

W3416 California Avocado

128 oz.

W3417 Miss Golightly

128 oz.

W3418 Swedish Blue

128 oz.

W3419 Drop of Gold

128 oz.

W3420 Caramelized

128 oz.

W3421 Francesca

128 oz.

FINISH

Sheen @ 85° 25-45

Sheen level depends on porosity of surface and various surface irregularities.

Resin Type: ACRYLIC BLEND

*Weight Solids: 49%

*Volume Solids: 38%

*Weight / Gallon (lbs): 10.5

*Viscosity: 97-107 KU

VOC: < 50 g/L

The addition of colorants may add VOCs.

FLASHPOINT

N/A

COVERAGE RATE

Coverage: Up to 400 sq. ft. per gallon depending on the surface texture, porosity and the application method. Does not include the loss of material from spraying.

COMPLIES WITH THE BELOW AS OF 2/10/2015

SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES		

RECOMMENDED FILM THICKNESS

At 300 sq. ft. per gallon:

Wet: 5.3 mils; **Dry:** 2.1 mils

At 400 sq. ft. per gallon:

Wet: 4.0 mils; **Dry:** 1.6 mils

DO NOT THIN. Product is formulated for use at package consistency only. Intermix containers of same product to ensure color and sheen uniformity.

APPLICATION

Airless Spray:

Tip: .015" - .021"

Filter: 60 mesh

PSI: Fluid pressure of 1,500 - 2,200

Roller:

Smooth Surfaces: 3/8" - 1/2" nap

Rough Surfaces: 1/2" - 3/4" nap

Brush:

Nylon / Polyester Blend

DRY TIME @ 77°F and 50% RH:

To Touch: 2 hours

To Recoat: 4 hours

Full Cure: 2 weeks

Darker colors may require additional dry time between coats. Cooler temperatures or higher humidity may prolong drying time.

SURFACE PREPARATION

All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

New Drywall:

All drywall surfaces should be sufficiently sanded smooth. Remove any remaining drywall dust prior to priming. Allow all drywall compounds to dry completely prior to coating.

* Numbers given here are from Ultra Bright White/ Base 1.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a technical service representative, call 1-866-275-5459 (1-866-ASK-KILZ) • www.kilz.com



INTERIOR/EXTERIOR SATIN PAINT



SURFACE PREPARATION *(CONTINUED)*

Previously Painted Drywall:

Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a wiping cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

Glossy Surfaces:

For maximum adhesion, scuff sand the surface before coating.

New Wood:

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

Remove mill glaze with sandpaper. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

Previously Painted Wood:

Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a tack or wiping cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

New Plaster:

New plaster should be thoroughly dried out and cured for a minimum of 30 days before painting. When cured, clean using a mixed solution of one part vinegar and one part water to remove efflorescence and neutralize.

Previously Painted Plaster:

Remove all loose and peeling paint and all other foreign substances. Clean any dirt and grease by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Set nails and fill holes, scratches, and gouges with the appropriate spackling material and let dry completely and sand smooth. Remove all dust with a tack cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

Masonry:

All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using a product such as KILZ® CONCRETE & MASONRY CLEANER & Etcher No.L0502 or with mechanical means.

Stainblocking:

For unpainted or heavily stained surfaces, prime using a product such as KILZ PREMIUM Primer/sealer/stainblocker. After priming, test for stain bleed-through by applying the topcoat to a small section. If the stain bleeds through the topcoat, apply a second coat of a primer and test again before top-coating the entire area. If bleeding continues, a longer dry time of the primer may be needed before top-coating.

Ferrous and Non-Ferrous Metal:

The oil film on new non-ferrous metal must be removed before it is painted. Remove oil film with a detergent and water solution. For better paint adhesion, sand the surface with sandpaper, steel wool, or by using a product such as KILZ CONCRETE & MASONRY CLEANER & ETCHER No. L0502. Clean by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water.

Metal:

Remove all rust and mill scale using sandpaper, steel wool, abrasive blasting, or other abrading methods to create a profile on the metal's surface. New Surfaces: Clean the metal by scrubbing the surface with a detergent and water solution, followed by a thorough rinsing with clean water. Bare metal must be primed the same day it is cleaned.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

RECOMMENDED PRIMER/SYSTEMS

PROPERLY PREPARED NEW SURFACES:

Drywall, Plaster, Masonry and Wood:

- 2 coats of KILZ SELECT LOOK Paint is minimum required for new or uncoated surfaces and surfaces with severe tannin and stains.

Ferrous & Non-Ferrous Metals:

- For previously painted metal surfaces, use KILZ PREMIUM Water Based Interior/Exterior Primer.

PREVIOUSLY PAINTED SURFACES:

- Use a full coat, or spot prime repaired surfaces with heavy stains, including tannin, with KILZ SELECT LOOK Paint.

CLEAN UP & DISPOSAL

Clean all tools and equipment with water. For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS

- **IMPORTANT!** Do not open can without reading instructions.
- For tint bases-do not use without addition of colorant.
- Do not use on floors.
- Do not use when air and surface temperature are below 50°F or above 90°F.
- Shelf life under normal conditions / 2 years unopened.
- Keep from freezing.

GENERAL INFORMATION



WARNING: Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

FIRST AID: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.

* Numbers given here are from Ultra Bright White/ Base 1.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a technical service representative, call 1-866-275-5459 (1-866-ASK-KILZ) • www.kilz.com