



## WOOD STAIN & FINISH STRIPPER



### PRODUCT INFORMATION

KILZ® Wood Stain & Finish Stripper is designed to remove oil-based, latex-based, and 100% acrylic finishes such as semi-transparent stains, solid color stains and clear sealers. It also removes loose wood fibers to help ensure a sound surface prior to staining or painting. Created especially for use on wood deck and siding surfaces.

### RECOMMENDED USES

To remove exterior latex-based, oil-based and 100% acrylic coatings that are applied to:

- Wood Decks
- Siding
- Fences
- Shakes
- Shingles

Not for interior use.

### PRODUCT SPECIFICATIONS

**Tint Bases/Max Tint Load:**

No. L050701 128 oz

**Active Type:** Sodium Hydroxide

**Weight per Gallon:** 8.9 lbs

**% Solids by Weight:** 11.5%

**VOC:** 4.1 wt %

**Flash Point:** N/A

**Viscosity:** N/A

**Coverage:** 50-150 Sq. Ft./Gal., depending on application method and substrate porosity.

### APPLICATION

**Brush:** Nylon/polyester

**Roller:** 3/8"-1/2" nap

**Airless Sprayer:** Not recommended

**Dry Time:** @ 77° & 50% RH

**To Recoat:** 24 hours

### SURFACE PREPARATION

Be sure to have a source for water, hose with nozzle and stiff bristle broom or brush and a product such as KILZ® Wood Cleaner & Brightener. DO NOT THIN PRODUCT. Do not apply in direct sunlight or on hot surfaces. Dampen nearby foliage with water and cover with plastic drop cloths.

**Wear protective clothing, goggles, acid resistant gloves, and NIOSH approved respirator.** Conduct a small test patch in an inconspicuous area to ensure product performance. Prevent all rinse solution from entering storm drains.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### CLEAN UP

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

### CAUTIONS/LIMITATIONS

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid applying in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

COMPLIES WITH THE BELOW AS OF 9/1/2014			
CARB	YES		

### GENERAL INFORMATION



**Danger!** Causes severe skin burns and serious eye damage. May be corrosive to metals. Wear protective clothing, gloves, eye, and face protection. Do not breathe vapors or spray mist. Do not eat, drink, or smoke when using this product. Wash hands thoroughly after handling. Wash contaminated clothing before use. Keep only in original, corrosive resistant container and store locked up. Dispose of unused contents, container and other contaminated waste in accordance with local, state, federal and provincial regulations.

**First aid: If in eyes:** Rinse cautiously with water for several minutes. Remove contacts if present and easy to do. Continue rinsing and get medical attention immediately. **If on skin or hair:** Immediately remove all contaminated clothing, rinse skin with water and get medical attention. **If inhaled:** Leave the area if you experience difficulty breathing, headaches, or dizziness to obtain fresh air and keep at rest in a position comfortable for breathing. If difficulty continues, get medical attention immediately. **If swallowed:** Rinse mouth. Do not induce vomiting. Get medical attention immediately.