



**INTERIOR MULTI-SURFACE WATER-BASED PRIMER**  
NO. L2011



**PRODUCT INFORMATION**

KILZ® 1 STANDARD Primer is designed for use on multiple interior surfaces. It helps save cost by reducing the number of coats of paint needed to achieve optimal results. It's ready to brush, roll or spray and can be topcoated after one hour with latex or oil-based paint. Use KILZ 1 STANDARD Primer on almost all interior surfaces including wood, drywall, plaster, brick and masonry. Not recommended for flooring, glossy surfaces, mold and mildew prone surfaces or for stainblocking.

**RECOMMENDED USES:**

Ideal for properly prepared coated and uncoated substrates such as:

- Wood
- Brick
- Drywall
- Interior Paneling (Wood/Masonry)
- Plaster
- Masonry

**PRODUCT SPECIFICATIONS:**

**Tint Bases/Max Tint Load:**

No. L2011 128 oz / 2 oz

**Sheen:** < 10.0 @ 85°

Sheen levels depend on porosity and various surface irregularities.

**Resin Type:** Acrylic

**Weight per Gallon:** 10.25 lbs.

**% Solids by Volume:** 20%

**% Solids by Weight:** 35%

**Flash Point:** N/A

**Viscosity:** 90 – 100 KU

**Recommended Film Thickness:**

Wet: 6.0 mils / Dry: 1.2 mils @ 250 sq ft/gal

Wet: 4.0 mils / Dry: 0.8 mils @ 400 sq ft/gal

**Coverage:** 300 – 400 sq ft/gal depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

**APPLICATION:**

**Brush:** Nylon/polyester blend

**Roller:** 3/8" – 1/2" nap

**Airless Spray:** Fluid pressure of 2,500 - 3,200 psi

**Tip:** .017" – .021"

**Thinning:** Not recommended. Product is formulated for use at package consistency only.

**Dry Time:** @ 77°F (25°C), 50% RH

Longer dry time required in cooler temperatures and in higher humidity.

**To Touch:** 30 Minutes

**To Recoat:** 1 hour

**SURFACE PREPARATION:**

Complete all patching, repairs and sanding before applying KILZ 1 STANDARD Primer.

The surface must be clean, free of dust, grease, wax, peeling paint, mold, mildew and wallpaper paste. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

**Peeling or Checked Paint:** crape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.†

**Glossy Surfaces:** KILZ® PREMIUM and KILZ 2® Primers are recommended for use over properly prepared glossy surfaces. However KILZ 1 STANDARD Primer may be used if the glossy surface is scuff sanded thoroughly to maximize adhesion.

**Masonry, Brick, Stucco and Plaster:** KILZ 1 STANDARD Primer may be used on clean, dry, aged masonry surfaces that have cured (dried) at least 30 days. If masonry has been cured less than 30 days, use a product such as KILZ PREMIUM Interior/Exterior Water-Base Primer.

**Mold or Mildew Covered Surfaces:** Wash the area with a mildew remover, rinse with water and allow to dry before priming. NOTE: KILZ KITCHEN & BATH, and KILZ PREMIUM Primers are recommended for mildew-prone surfaces.

**Fire Restoration:** Not recommended for fire restoration.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**CLEAN UP:**

Clean all tools and equipment with warm, soapy water. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. Do not dispose of this product down a drain. Please consider donating any unused product.

COMPLIES WITH THE BELOW AS OF 12/20/2018			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES		

For disposal of empty containers and unused product, contact your household refuse collection service.

**CAUTIONS/LIMITATIONS:**

- **IMPORTANT!** Do not open can without reading instructions.
- Do not use when air and surface temperatures are below 50°F or above 90°F.
- Shelf life under normal conditions is 2 years unopened.

**GENERAL INFORMATION:**

**WARNING**  
Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**CAUTION IRRITANT** MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID REATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Store locked up in a cool, well-ventilated place. Dispose of unused contents, container, and other contaminated wastes in accordance with local, state, federal, and provincial regulations.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**