



CLEAR SEALER & BONDING PRIMER

NO. L2201



PRODUCT INFORMATION

KILZ KLEAR® Clear Sealer & Bonding Primer is a high performance fast-dry multi-surface clear primer developed to seal porous surfaces inside and outside your home. Particularly effective for 'same color painting', KILZ KLEAR Primer will bond and seal porous and chalky surfaces with little change to current color. KILZ KLEAR Primer is a tough, flexible and breathable film to offer years of service. KILZ KLEAR Primer may also be used to seal highly porous surfaces with a transparent flat finish. Suitable for sealing torn drywall facing paper, dried wallcovering adhesive, 'hot' joint compounds, concrete and stucco with surface pH up to 12.5. Not recommended for floors.

RECOMMENDED USES:

Use KILZ KLEAR Primer on interior and exterior surfaces, including:

- Wood
- Drywall
- Plaster
- Stucco
- Brick
- Concrete
- Masonry
- Paneling
- T1-11 Siding
- Non-Ferrous Metal
- Architectural Plastics†
- Properly Prepared Glossy Surfaces*

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. L2201 128 oz / 2 oz

Sheen: < 10 @ 85°

Sheen levels depend on porosity and various surface irregularities.

Resin Type: Styrene Acrylic

Weight per Gallon: 8.6 lbs

% Solids by Volume: 17.5%

% Solids by Weight: 19.7%

VOC: < 100 g/L

Flash Point: N/A

Viscosity: 60 - 70 KU

Recommended Film Thickness:

Wet: 5.3 mils / Dry: 0.9 mils @ 300 Sq. Ft./Gal.

Wet: 4.0 mils / Dry: 0.7 mils @ 400 Sq. Ft./Gal.

Coverage: 300 - 400 Sq. Ft./Gal. depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon / Polyester

Roller: 3/8" - 1/2" nap

Airless Spray: Fluid pressure of 1,800 - 3,000 psi

Tip: .015" - .017"

Filter: 60 mesh

Thinning: Not recommended. Product is formulated for use at package consistency only.

Dry Time: @ 77°F, 50% RH

Longer dry time required in cooler temperatures and in higher humidity.

To Touch: 30 Minutes

To Recoat: 1 hour

SURFACE PREPARATION:

All surfaces must be clean, free of dust, chalk, oil, grease, wax polish, mold and mildew, loose peeling paint, rust and all other foreign substances.*

Wash: If washing is necessary, use a non-soapy detergent or TSP substitute. Rinse well and allow to dry.

Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.*

Glossy Surfaces: scuff and sand to de-gloss and wipe clean before application.*

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 1/1/2019

| | | | |
|--------|-----|-------------|-----|
| SCAQMD | YES | LADCO | YES |
| CARB | YES | AIM | YES |
| OTC | YES | GREENGUARD® | YES |

CAUTIONS/LIMITATIONS:

- IMPORTANT! Do not open can without reading instructions.
- Do not use on floors.
- Do not use when air and surface temperatures are below 50° or above 90°.
- Shelf life under normal conditions is 2 years unopened.

GENERAL INFORMATION:



WARNING Cancer and Reproductive Harm—
www.P65Warnings.ca.gov

WARNING IRRITANT. HARMFUL IF SWALLOWED. CONTAINS ETHYLENE GLYCOL. Avoid contact with eyes. May cause eye, nose and throat irritation. Avoid breathing of dust, vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor/ mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH / MSHA TC 23C or equivalent) during and after application. Follow respirator manufacturer's direction for respirator use. Close container after each use. Wash thoroughly after handling and before smoking and eating.

FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.

USE ONLY WITH ADEQUATE VENTILATION

**KEEP OUT OF REACH OF CHILDREN
– DO NOT TAKE INTERNALLY**