



WET-LOOK SEALER



PRODUCT INFORMATION

KILZ® Wet-Look Sealer is a clear, non-yellowing, high solids, acrylic-based masonry sealer. It is formulated to seal, protect and beautify concrete and masonry surfaces with a high gloss, wet-look finish. KILZ Wet-Look Sealer is also an excellent topcoat for paints and stains.

RECOMMENDED USES:

Use on previously coated or uncoated, vertical or horizontal, interior or exterior surfaces such as: pavers, concrete, and unglazed tiles, brick, aggregate, natural and artificial stone, masonry and stucco. Not recommended for use on wood, metal, granite, marble, terrazzo, areas immediately adjacent to pools or areas subject to hydrostatic pressure. Do not use over oil-based products. CAUTION: Sealed surfaces may become slippery when wet. Use caution when walking on surface when moisture is present. Apply in sections and walk on dry areas during application.

PRODUCT SPECIFICATIONS

Fill Level:

No. L3902 Wet Look High Gloss 128 oz

Sheen/Gloss: 55-70 @ 20°

Resin Type: Acrylic

Weight per Gallon: 8.5 lbs

% Solids by Volume: 25.4%

% Solids by Weight: 27.6%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 12-24 sec, #2 Zahn Cup

Recommended Film Thickness:

1st Coat Wet: 8.0 Dry: 2.0 mils @ 200 Sq. Ft./Gal.

2nd Coat Wet: 3.5 Dry: 0.9 mils @ 450 Sq. Ft./Gal.

Coverage: 200-450 Sq. Ft./Gal. depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION

Brush: Nylon/polyester

Roller: 3/8"-1/2" nap

Pump Sprayer: high quality with an adjustable tip

Thinning: Do Not Thin

Dry Time: @ 77° & 50% RH

To Touch: 1 hour

To Recoat: 4 hours

Allow surface to dry 24-48 hours before subjecting surface to heavy foot traffic.

Longer dry time may be required in cooler temperatures and higher humidity.

SURFACE PREPARATION

Masonry: Concrete, Concrete Masonry Units (CMUs), Split-Faced Block: New and Uncoated: All masonry surfaces must be cured at least 30 days before painting. The pH must be 10.0 or lower prior to coating. Smooth masonry may require an adequate profile for adhesion. For all other smooth concrete, create a profile using a product such as KILZ Concrete & Masonry Cleaner & Etcher or with mechanical means. Remove loose aggregate and debris using a product such as KILZ Concrete & Masonry Degreaser & Cleaner.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

RECOMMENDED PRIMER/SYSTEMS

New or uncoated Masonry:

• All surfaces must be clean, free of dust, chalk, oil, grease, wax, polish, mold and mildew stains, loose and peeling paint, rust and all other foreign substances.

CLEAN UP

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2014			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	99
OTC	YES		

CAUTIONS/LIMITATIONS

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 80°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24-48 hours.
- Allow 72 hours before repositioning furniture
- Allow two weeks before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION



Warning! Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.