



OVER ARMOR® SMOOTH



PRODUCT INFORMATION

Over Armor® Smooth Solid Color Coating is an innovative solid color coating that will bring your old, weathered wood or concrete back to life. The advanced 100% acrylic resin creates a durable coating on your tired deck, rejuvenating its look. Over Armour Coating is designed to conceal splinters & cracks up to 1/4" and creates a smooth, slip-resistant finish. It is available in a selection of popular wood and concrete custom colors.

RECOMMENDED USES:

Recommended for properly prepared exterior weathered or cracked horizontal and vertical surfaces such as:

- Wood
- Composite
- Concrete

Do not use on drivable surfaces such as garage floors and driveways.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. L3942 116 oz./14 oz.

Resin Type: 100% Acrylic

Weight per Gallon: 10.77 lbs

% Solids by Volume: 51.0%

% Solids by Weight: 62.5%

VOC: <50 g/L

Flash Point: N/A

Viscosity: 95-105 KU (Paste Paddle)

Recommended Film Thickness:

Wet: 14.5 mils Dry: 10.9 mils @ 75 Sq. Ft./Gal. per 2 coats (5.4 mils Dry per coat)

Coverage: 75 Sq. Ft./Gal. 2 coats required.

APPLICATION:

Brush: Nylon/polyester brush

Roller: 1/4" - 1/2" nap

Airless Spray: At packaged consistency

Tip: .027"-.035" with no filter at 2400-3200 psi

Dry Time: @ 77° & 50% RH

To Recoat: 4-6 hours

Light Foot Traffic: 24-48 hours

Full Cure: 72 hours

- For nail holes and cracks up to 1/4", completely fill in with Over Armor using a nylon/polyester brush and allow to dry prior to rolling. Deep nail holes and cracks may require additional filling.
- Use pressure while rolling and apply generously.

SURFACE PREPARATION:

The following steps and products are required: All surfaces must be clean, sound, dry and free of any dirt, oil, and grease before application. **Wood Surfaces:** Replace rotting or unstable boards and remove loose splinters. If you remove mildew stains and dirt with a product such as KILZ Wood Cleaner & Brightener, then you must use a product such as KILZ Wood Stain & Finish Stripper to remove all loose wood fibers, peeling paint/stain or deteriorated coatings prior to application of KILZ Over Armor Solid Color Coating. On new wood, use a product such as KILZ Wood Cleaner & Brightener to remove mill glaze and open the pores of the wood. Rinse thoroughly and allow to dry before coating.

Concrete Surfaces: Avoid areas that are structurally weak or subject to hydrostatic pressure up to 8 psi. Allow new surfaces to cure for 30 days. Use a product such as KILZ Concrete & Masonry Paint Stripper to strip peeling coating. Use a product such as KILZ Concrete & Masonry Cleaner & Etcher to clean and etch uncoated concrete or KILZ Concrete & Masonry Degreaser & Cleaner.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP:

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2014			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	FLAME SPREAD/CLASS A	YES

CAUTIONS/LIMITATIONS:

- Protect from freezing
- Do not use without the addition of tinting colorants
- Do not use if rain is expected within 24 hours
- DO NOT THIN PRODUCT
- Avoid applying paint in direct sunlight or hot surfaces
- Test product for color on a small hidden area before proceeding
- Painted surfaces may become slippery when wet
- Shelf life under normal conditions is 2 years (unopened containers)
- Do not use on drivable surfaces such as garage floors and driveways.
- Temperature Range: 50-90°F (10-32°C)

GENERAL INFORMATION:



Warning! Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.