



SEMI-TRANSPARENT CONCRETE STAIN



PRODUCT INFORMATION

KILZ® Semi-Transparent Concrete Stain provides the variation of color found in some natural stone. Surface imperfections, concrete composition, texture and application technique will affect the finished appearance. For a uniform solid color, use a product such as KILZ Solid Color Concrete Stain.

RECOMMENDED USES:

This product is ideal for patios, pavers, driveways, walkways, garage floors. For use on uncoated and unsealed, properly prepared, interior or exterior surfaces such as:

- Concrete Floors
- Brick
- Masonry

The composition of concrete varies; therefore, the lack of proper surface preparation and/or excessive application can lead to automobile tires lifting the product from the surface. For added protection, use a product such as KILZ Wet-Look Sealer for a high-gloss finish or a product such as KILZ Low-Lustre Sealer for a low-gloss finish. Allow stain at least 4 hours to dry before topcoating per label instructions.

PRODUCT SPECIFICATIONS

Tint Bases/Max Tint Load:

No. L3973 126 oz / 4 oz

Sheen: N/A

Sheen levels depend on porosity and various surface irregularities.

Resin Type: Silicized 100% Styrene Acrylic

Weight per Gallon: 8.5 lbs

% Solids by Volume: 17%

% Solids by Weight: 19%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 35-55 KU

Recommended Film Thickness:

Wet: 9.1 Dry: 1.6 mils @ 250 sq. ft./gal.

Wet: 4.6 Dry: 0.8 mils @ 500 sq. ft./gal.

Coverage: 250-500 sq. ft./gal. depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION

Brush: Nylon/polyester

Roller: 3/8" - 1/2" nap

Pump Sprayer: This product may be sprayed with a high quality pump sprayer

Airless Spray: .015" - .019"

Filter: 60 mesh

Thinning: Use at packaged consistency; DO NOT THIN.

Dry Time: @ 77° & 50% RH

To Touch: 1 hour

To Recoat: 4 hours

Longer dry time may be required in cooler temperatures and higher humidity.

SURFACE PREPARATION

Masonry: New concrete must cure for a minimum of 30 days. Remove old coating or sealer, if present, using a product such as KILZ Concrete & Masonry Paint Stripper. Follow all label instructions. Test: Sprinkle a few drops of water onto the surface. If water is quickly absorbed, the surface is ready. If not absorbed, re-etch. For proper penetration and adhesion of topcoat, use a product such as KILZ Concrete & Masonry Cleaner & Etcher to clean and etch the surface. Follow all label instructions. Remove mildew stains with a mold and mildew stain remover. Follow all label instructions. Apply a product such as KILZ Bonding Primer to increase adhesion of topcoat to the surface. Follow all label instructions. Do not thin. Intermix cans of same products to ensure color uniformity. Stir thoroughly before and during application.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2014

SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES		

CAUTIONS/LIMITATIONS

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid light foot traffic for 24 hours.
- Avoid heavy foot traffic, repositioning of furniture or automotive traffic for 72 hours.
- Park tires on corrugated cardboard for 7 days after applying stain.
- Allow 30 days before washing or cleaning for full cure.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION



Warning! Causes eye and skin irritation. Harmful if swallowed. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Collect spillage and avoid release to the environment. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If swallowed:** Rinse mouth and get medical attention if you feel unwell. **If on skin:** Wash with plenty of soap and water.