



## KILZ® CHALK STYLE PAINT



### PRODUCT INFORMATION

Easily add history and character to any surface with KILZ® CHALK STYLE PAINT. It goes on thick for excellent hide, and requires very little surface preparation. Depending on the vision you have for the project, simply apply 1 or 2 coats on a clean, dust-free, or lightly sanded surface. For interior use only. Do not use in high-humidity environments. To enhance durability, seal the surface afterward with KILZ CLEAR SEALING WAX. An "antique" look can be achieved by applying two contrasting colors, distressing with sandpaper, and sealing with KILZ DARK SEALING WAX.

KILZ Products have been trusted for over 40 years to deliver quality finishes. Whether you're reclaiming, refinishing, remodeling, or renovating, if you have a vision you want to bring to life, you can count on KILZ Products to get it done right!

### IDEAL FOR

KILZ CHALK STYLE PAINT can be applied over most existing finishes with little surface preparation. Use to "up-cycle" vintage furniture. Apply to old or new wood, cast stone, concrete, or even metal surfaces<sup>1</sup>. **Do not use on horizontal surfaces subject to foot traffic.**

### PRODUCT SPECIFICATIONS

#### FILL LEVEL/ MAXIMUM TINT

**L5401 KILZ CHALK STYLE PAINT Base 1 White**  
31 fl. oz./916 ml

**L5403 KILZ CHALK STYLE PAINT Base 3**  
29 fl. oz./857 ml

**L5405 KILZ CHALK STYLE PAINT White**  
32 fl. oz./946 ml

**L5406 KILZ CHALK STYLE PAINT Cameo Coral**  
32 fl. oz./946 ml

**L5407 KILZ CHALK STYLE PAINT Blue Juniper**  
32 fl. oz./946 ml

**L5408 KILZ CHALK STYLE PAINT Chalk Gray**  
32 fl. oz./946 ml

**L5409 KILZ CHALK STYLE PAINT Smokey Eyes**  
32 fl. oz./946 ml

**L5410 KILZ CHALK STYPE PAINT Toasted Poppyseed**  
32 fl. oz./946 ml

#### FINISH

Sheen @ 85° <5

*Sheen level depends on porosity of surface and various surface irregularities.*

#### Resin Type: MODIFIED ACRYLIC

\*Weight per Gallon: 12.5 +/- 2% lbs.

\*% Solids by Volume: 38 +/- 2%

\*% Solids by Weight: 59 +/- 2%

#### VOC: < 50 g/L

The addition of colorants may add VOCs.

#### FLASHPOINT

N/A

#### \*VISCOSITY

85-95 KU

#### COVERAGE RATE

60-100 sq. ft. of coverage per quart with two coats depending on your technique and surface porosity.

#### \*RECOMMENDED FILM THICKNESS

Film thickness depends on porosity of surface and various substrate irregularities.

At 60 sq. ft. per Quart:

**Wet:** 6.5 mils; **Dry:** 2.5 mils

At 100 sq. ft. per Quart:

**Wet:** 4.0 mils; **Dry:** 1.5 mils

### APPLICATION

- Shake the container thoroughly before opening for application
- Use on properly prepared surfaces
- Use product when the surface and air temperatures are between 50-90°F and will remain in that range for at least 4 hours after applying

#### Roller:

High Density Foam Roller

3/8" - 1/2" Synthetic Roller

#### Brush:

Nylon / Polyester Blend

**Note:** This product is formulated to be rich and concentrated to provide excellent hide and coverage. If you find this product to be too thick, add up to 2 oz. of water per quart to thin it to the desired thickness for smooth and easy application.

#### DRY TIME @ 77°F and 50% RH:

To Touch: 1 hour

To Recoat: 2 hours

Darker colors may require additional dry time between coats. Cooler temperatures or higher humidity may prolong drying time.

### SURFACE PREPARATION

- Before applying KILZ CHALK STYLE PAINT, clean the surface to make sure it is free of loose or peeling paint, mold and mildew stains, rust and other dirt and debris.
- We recommend lightly sanding glossy surfaces and repairing any imperfections.
- Remove all dust with a damp cloth and allow to dry. Use KILZ CHALK STYLE PAINT on properly prepared uncoated or painted interior surfaces.
- For wood that contains tannins, such as Redwood and Cedar, a coat of primer such as KILZ PREMIUM Interior/Exterior water-based primer is recommended

#### Glossy Surfaces:

- For optimal adhesion to difficult surfaces, use KILZ PREMIUM Primer
- Follow the instructions on the back of the primer label and top coat it with KILZ CHALK STYLE PAINT

#### New Wood:

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection. Remove mill glaze with sandpaper. Set nails and fill holes, scratches, and gouges with the appropriate wood filler and let dry completely. Remove all dust with a wiping cloth. Fill all gaps with a paintable caulking, and allow to completely dry prior to coating.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit [www.epa.gov/lead](http://www.epa.gov/lead).

### CLEAN UP & DISPOSAL

Clean all tools and equipment with water. For disposal of empty containers and unused product, contact your household refuse collection service.

### CAUTIONS/LIMITATIONS

- **IMPORTANT!** Do not open can without reading instructions.
- Shake can thoroughly before opening for application.
- Stir before and during application.
- For tint bases-do not use without addition of colorant.
- Do not use on floors.
- Do not use when air and surface temperature are below 50°F or above 90°F.
- Shelf life under normal conditions is 2 years unopened.
- Keep from freezing.

<sup>1</sup>Base 1

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a technical service representative, call 1-866-275-5459 (1-866-ASK-KILZ) • [www.kilz.com](http://www.kilz.com)



**KILZ® CHALK STYLE PAINT**  
**NO. L5400**



**GENERAL INFORMATION:**



**WARNING:** Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**FIRST AID: If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water.

**If swallowed:** Rinse mouth and get medical attention if you feel unwell.