



WEATHERPROOFING TRANSPARENT WOOD FINISH



PRODUCT INFORMATION

KILZ® Weatherproofing Transparent Wood Finish has a 100% acrylic formula that seals out the elements and the sun's harmful UV rays on decks, fences and siding. It's available in 3 pre-mixed colors as well as 6 custom colors so you can get the look you want while preserving your valuable investment.

RECOMMENDED USES:

For wood substrates only. Recommended for properly prepared new to slightly weathered, unsealed exterior wood surfaces (0-5 years exposure) such as:

- Decks
- Shingles
- Wood Patio Furniture
- Railings
- Siding
- Shakes
- Fences

PRODUCT SPECIFICATIONS

Tint Bases/Max Tint Load:

No. L8200 Natural 124 oz. / 4 oz.

Pre-Mixed Colors:

- No. L8200 Natural
- No. L8201 Cedar Naturaltone
- No. L8202 Redwood

Resin Type: Advanced 100% Acrylic

Weight per Gallon: 8.7 lbs

% Solids by Volume: 26%

% Solids by Weight: 28%

VOC: <275 g/L

Flash Point: N/A

Viscosity: 15-30 sec #2 Zahn Cup

Recommended Film Thickness:

- Wet: 5.4 Dry: 1.4 mils @ 300 sq.ft./gal.
- Wet: 2.7 Dry: 0.7 mils @ 600 sq.ft./gal.

Coverage: 300-600 sq.ft./gal., depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION

Brush: Nylon/polyester

Roller: 3/8" nap

Pad Applicator

Airless Spray: At packaged consistency

Tip: .015" - .019"

Filter: 60 mesh

Dry Time: @ 77° & 50% RH

To Recoat: 1-2 hours

Light Foot Traffic: 24-48 hours

Full Cure: 72 hours

Use a nylon/polyester brush for areas requiring more accuracy. Use of rollers should be limited to rough surfaces only. Work in small sections lightly saturating the surface and immediately back-brush or use pad applicator to eliminate puddling, remove excess and evenly distribute the finish. Maintain a wet edge when applying. Apply product end-to-end or to board lengths to prevent lap marks. Over application of finish will lead to surface failure including peeling and cracking. Avoid applying finish too heavily. Two thin coats required. For optimum performance, coat all accessible sides.

SURFACE PREPARATION

The following steps and products are recommended for best results: (Proper surface preparation is required.) For failing coatings or to remove loose wood fibers, use a product such as KILZ Wood Stain & Finish Stripper followed by KILZ Wood Cleaner & Brightener to neutralize the wood. When KILZ Wood Stain & Finish Stripper is not needed, a product such as KILZ Wood Cleaner & Brightener **MUST** be used to remove mill glaze and clean the wood surface. After using either KILZ Wood Stain & Finish Stripper or KILZ Wood Cleaner & Brightener, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface. Allow the area to dry at least 24 hours before coating. Lightly sand to remove remaining wood fibers/fuzz. See www.kilz.com for additional product information.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2014			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	FLAME SPREAD/CLASS A	YES

CAUTIONS/LIMITATIONS

- Protect from freezing
- Do not use if rain is expected within 24 hours
- **DO NOT THIN PRODUCT**
- Avoid applying stain in direct sunlight or to hot surfaces
- Test product for color on a small hidden area before proceeding
- Over application of stain will lead to surface failure including peeling & cracking
- Stained surfaces may become slippery when wet.
- Shelf life under normal conditions is 2 years (unopened containers)
- Temperature Range: 40-90°F

GENERAL INFORMATION



Warning! Causes eye and skin irritation. Harmful if swallowed. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage and avoid release to the environment. Dispose of unused contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.