



WEATHERPROOFING SOLID COLOR STAIN



PRODUCT INFORMATION

KILZ® Weatherproofing Solid Color Stain has a 100% acrylic latex formula that provides excellent adhesion and forms a highly protective and durable finish which resists scuffing, cracking, peeling and blistering.

RECOMMENDED USES:

Exterior properly prepared wood and composite surfaces such as smooth or rough sawn wood surfaces such as:

- Plywood
- Shingles
- Decks
- Fences
- Shakes
- Railings
- Patio Covers
- Siding
- Composites

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

- No. L841111 124 oz
- No. L841011 116 oz

Resin Type: Advanced 100% Acrylic

Weight per Gallon: 10.3 lbs

% Solids by Volume: 37%

% Solids by Weight: 49%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 68-75 KU

Recommended Film Thickness:

- Wet: 8.0 Dry: 3.0 mils @ 200 sq. ft./Gal.
- Wet: 4.0 Dry: 1.5 mils @ 400 sq. ft./Gal.
- Wet: 2.0 Dry: 0. mils @ 800 sq. ft./gal (second coat only)

Coverage: 200-800 sq. ft./gal., depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/8" nap

Pad Applicator

Airless Spray: At packaged consistency

Tip: .015" - .019"

Filter: 60 mesh

Dry Time: @ 77° & 50% RH

- To Recoat:** 1-2 hours
- Light Foot Traffic:** 24-48 hours
- Full Cure:** 72 hours

- Follow spraying immediately with a pad, back brushing or back rolling for a uniform appearance.
- Work in small sections lightly saturating the surface and immediately back-brush or use pad applicator to eliminate puddling; remove excess stain and evenly distribute the finish. Maintain a wet edge when applying.

SURFACE PREPARATION:

The following steps and products are recommended for best results: If you use a product such as KILZ Wood Stain & Finish Stripper to remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new weathered wood, then you must use a product such as KILZ Wood Cleaner & Brightener to clean, brighten & neutralize the wood. If you do not use a product such as KILZ Wood Stain & Finish Stripper, then use a product such as KILZ Wood Cleaner & Brightener to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae & fungus. Rinse thoroughly and allow to dry before coating. On new wood, use a product such as KILZ Wood Cleaner & Brightener to remove mill glaze and open the pores of the wood. Lightly sand to remove remaining wood fibers/fuzz.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

RECOMMENDED PRIMER/SYSTEMS:

Wood & Tannin/Stain-blocking:

- KILZ PREMIUM Interior/Exterior Water-Base Primer

PREVIOUSLY PAINTED SURFACES:

- KILZ PREMIUM Interior/Exterior Water-Base Primer

COMPLIES WITH THE BELOW AS OF 9/1/2014			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	MPI#	16

CLEAN UP:

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not use without the addition of tinting colorants.
- Do not use if rain is expected within 24 hours.
- DO NOT THIN PRODUCT.
- Avoid applying stain in direct sunlight or hot surfaces.
- Test product for color on a small hidden area before proceeding.
- Over application of stain will lead to surface failure including peeling & cracking.
- Stained surfaces may become slippery when wet.
- Shelf life under normal conditions is 2 years (unopened containers).
- Temperature Range: 40-90°F (4.5-32°C)

GENERAL INFORMATION:



Warning! Causes eye and skin irritation. Harmful if swallowed. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage and avoid release to the environment. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.