KILZ FLOOR COATINGS

OVER ARMOUR™

KILZ OVER ARMOUR™ DEEP BASE

OVER ARMOUR™ is a solid colour, lightly textured coating designed to bridge cracks, hide imperfections and give old, weathered wood a uniform look. Available in limited "wood stain" and "concrete" colours. Additionally, Over Armour can be used over cracked & weathered concrete.

AS OF 3/22/2011 COMPLIES OR IS CERTIFIED WITH:			
OTC	Yes	CARB	Yes
SCAQMD	Yes	MPI #	NA

WHERE TO USE

Recommended for properly prepared weathered or cracked horizontal wood and composite surfaces such as:

- Decks
- Porches
- Boat Docks

Also great for concrete surfaces such as:

- Pool Decks
- Patios
- Sidewalks

TINT BASES / MAX TINT LOAD

No. L3923 Deep Base
3.43 L / 414 mL
17.2 L / 2.07 L

COMPOSITION

Vehicle Type: 100% Acrylic
Volume Solids: 50.8% (+/-) 2%
Weight Solids: 62.3% (+/-) 2%
Weight / 3.79 L: 4.88 kg (+/-) 91 g
Viscosity: 92-97 KU (Paste Paddle)

VOC: < 50 g/L

FLASHPOINT

N/A

COVERAGE RATE

Coverage: 4.65m^2 Per 3.79 L. 2 coats required.

RECOMMENDED FILM THICKNESS

At 9.3 m^2 per 3.79 L per coat:
- Wet: 16 mils; Dry: 8.1 mils

At 4.65 m^2 per 3.79 L per coat:
- Wet: 32 mils; Dry: 16.3 mils

SURFACE PREPARATION† *(The following steps and products are recommended for best results.)*

- All surfaces must be clean, sound, dry and free of any dirt, oil, and grease before application.
- **Wood Surfaces:** Replace rotting or unstable boards and remove loose splinters.
- Remove mildew, stains, dirt, oil and grease with a product such as KILZ Wood Cleaner & Brightener prior to application.
- Use a product such as KILZ Wood Stain & Finish Stripper (must be followed by KILZ Wood Cleaner & Brightener) to remove all loose wood fibers, peeling paint/stain or deteriorated coatings prior to application of Over Armour.
- On new wood, use KILZ Wood Cleaner & Brightener to remove mill glaze and open the pores of the wood. Rinse thoroughly and allow to dry before coating.
- **Concrete Surfaces:** Avoid areas that are structurally weak or subject to hydrostatic pressure.
- Allow new surfaces to cure for 30 days.
- Use a product such as KILZ Concrete & Masonry Paint Stripper to strip peeling coating.
- Use a product such as KILZ Concrete & Masonry Cleaner & Etcher to clean and etch uncoated concrete surfaces prior to coating.

APPLICATION

- MUST PREP BEFORE USE.
- Wood surface must be completely dry prior to painting.
- Intermix multiple containers to ensure colour uniformity.
- Avoid exposure of container to direct sunlight
- Temperature Range: 4-32° C.

APPLICATION METHODS

- Nylon/polyester brush (for edges, corners and in between boards).
- 6 mm-15 mm nap roller. For smoother textures, use shorter nap.
- For nail holes and cracks up to 6mm, completely fill in with OVER ARMOUR coating using a nylon/polyester brush and allow to dry prior to rolling. Deep nail holes and cracks may require additional filling.
- Use pressure while rolling and apply generously.

DRY TIME*

- Recoat after 4-6 hours Wait 24-48 hours before light foot traffic. 72 hours for full cure. *Cool temperatures and/or high humidity will require additional drying time.
- 2 coats required.
- For optimum performance, coat all six sides of wood.

Masterchem Industries LLC

This information is provided "as is" and no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.

For MSDS or to consult with a technical service representative, call 1-866-774-6371 (1-866-PRIMER-1).Revised 9/2012

©2012 Masterchem Industries, 3135 Old Hwy M, Imperial, MO 63052-2834
1-877-KILZ-PRO • www.kilzpro-x.com
A Masco Company

KILZ FLOOR COATINGS
OVER ARMOUR™

KILZ OVER ARMOUR™ DEEP BASE

CLEAN UP & DISPOSAL
- Brushes and other equipment can be cleaned with warm, soapy water.
- For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS / LIMITATIONS
- **PROTECT FROM FREEZING**
- **DO NOT USE WITHOUT THE ADDITION OF TINTING COLOURANTS**
- **DO NOT USE IF RAIN IS EXPECTED WITHIN 24 HOURS**
- **DO NOT THIN PRODUCT**
- **AVOID APPLYING PAINT IN DIRECT SUNLIGHT OR TO HOT SURFACES**
- **TEST PRODUCT FOR COLOUR ON A SMALL HIDDEN AREA BEFORE PROCEEDING**
- **PAINTED SURFACES MAY BECOME SLIPPERY WHEN WET**
- **SHELF LIFE UNDER NORMAL CONDITIONS IS 2 YEARS (UNOPENED CONTAINERS)**

GENERAL INFORMATION
IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.

†WARNING! *If you scrape sand or remove old paint, you may release lead dust.* ***LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.*** *Wear a NIOSH-approved respir tor to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.*

WARNING: *This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.*

WARNING: *Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.*

WARNING! IRRITANT! ***HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.*** *To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air and use a properly fitted respirator (NIOSH approved for zorganic vapor with P Series particulate prefilter). Obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.*

FIRST AID
- *If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.*
- *In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention.*
- *For skin, wash thoroughly with soap and water.*
- *If swallowed, get medical attention immediately.*

CAUTION:
KEEP OUT OF REACH OF CHILDREN
DO NOT TAKE INTERNALLY.

This information is provided "as is" and no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information.

For MSDS or to consult with a technical service representative, call 1-866-774-6371 (1-866-PRIMER-1).Revised 9/2012

Masterchem Industries LLC

©2012 Masterchem Industries, 3135 Old Hwy M, Imperial, MO 63052-2834
1-877-KILZ-PRO • www.kilzpro-x.com
A Masco Company