



PROFESSIONAL INTERIOR DRYWALL PRIMER & SEALER
NO. PX010



PRODUCT INFORMATION

KILZ® PVA DRYWALL PRIMER is designed for use on new drywall. It is a fast drying, interior water-based primer formulated to prime and seal new, uncoated drywall and reduce the number of topcoats required to achieve a uniform, professional quality finish.

RECOMMENDED USES:

Recommended use on:

- New Uncoated Drywall/Gypsum Board

Designed for use under flat and low sheen paints only. Do not topcoat with glossy paint finishes.

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. PX010 640 oz. / 10 oz.

Resin Type: PVA

Weight per Gallon: 10.8 lbs.

% Solids by Volume: 27%

% Solids by Weight: 42%

VOC: < 100 g/L

Flash Point: N/A

Viscosity: 105 – 115 KU

Recommended Film Thickness:

Wet: 6.4 mils / Dry: 1.7 mils @ 250 sq ft/gal

Wet: 4.0 mils / Dry: 1.1 mils @ 400 sq ft/gal

Coverage: 250 – 400 sq ft/gal depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester blend

Roller: 3/8" – 1/2" nap

Airless Spray: Fluid pressure of 1,800 – 3,000 psi

Tip: .015" – .021"

Filter: 60 mesh

Dry Time: @ 77°F, 50% RH

Longer dry time required in cooler temperatures and in higher humidity.

To Touch: 30 minutes

To Recoat: 2 hours

SURFACE PREPARATION:

Cover all nail and screw heads with joint compound according to directions and sand to smooth surface.*

Tape drywall and apply joint compound and allow to fully cure according to directions prior to priming.

Sand to smooth surface before priming.*

Wipe off dust with a damp cloth, allow to dry thoroughly.

***WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit www.epa.gov/lead.

CLEAN UP:

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

IMPORTANT! Do not open can without reading instructions.

- Interior use only.
- For use on uncoated drywall only.
- Do not use on floors.
- Do not use when air and surface temperatures are below 50°F or above 90°F.
- Allow 2 weeks for full cure before washing or cleaning.
- Do not use over glossy surfaces.
- Shelf life under normal conditions is 2 years unopened.

COMPLIES WITH THE BELOW AS OF 1/1/2019			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	LEED v.3 (2009) [†]	YES

[†]Please visit www.usgbc.org/LEED for additional details.

GENERAL INFORMATION:

WARNING
Cancer and Reproductive Harm – www.P65Warnings.ca.gov

CAUTION IRRITANT Avoid contact with eyes. May cause eye, nose and throat irritation. Avoid breathing of dust, vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/ mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH / MSHA TC -23C or equivalent) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling and before smoking or eating.

FIRST AID: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush eyes immediately with plenty of water for at least 20 minutes and get medical attention.

USE ONLY WITH ADEQUATE VENTILATION

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.