TECHNICAL DATA SHEET

STAIN BLOCKING CEILING PAINT

PRODUCT INFORMATION

KILZ® Stainblocking Ceiling Paint is a unique combination of stainblocking technology and a coverage / dry time indicator. It rolls on easily with minimal spattering and a subtle pink color that quickly dries to white. It can be used on all interior ceilings.

RECOMMENDED USES:

Use on properly prepared interior surfaces, such as:

- Brick
- Drywall
- Masonry
- Painted Metal
- Paneling
- Plaster
- Properly Prepared Glossy Surfaces
- Stucco
- Wood

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:
No. 6800 128 oz / 2 oz
Tinting is not recommended for stainblocking applications.

Sheen: < 5.0 @ 85°
Sheen levels depend on porosity and various surface irregularities.

Resin Type: Acrylic Polymer

Weight per Gallon: 11.3 lbs ± 0.2

% Solids by Volume: 42% ± 2%

% Solids by Weight: 56% ± 2%

***VOC:** 49 g/L

Flash Point: N/A

Viscosity: 95 – 105 KU

Recommended Film Thickness:
Wet: 6.4 mils / Dry: 2.4 mils @ 250 sq ft/gal
Wet: 4.0 mils / Dry: 1.5 mils @ 400 sq ft/gal

Coverage: 250 – 400 sq. ft. (23 – 37 m^2) per gallon, depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: 1/2" – 3/4" nap

Airless Spray: Fluid pressure of 2,500 – 3,200

Tip: .015" – .019"

Filter: 60 mesh

Dry Time: @ 77°F, 50% RH
To Touch: 1 hour
To Recoat/Topcoat: 2 hours; 4 hours for maximum stainblocking
Longer dry time required in cooler temperatures and in higher humidity.

SURFACE PREPARATION:

The surface must be clean, free of dust, grease, wax, peeling paint, mold, mildew and wallpaper paste. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.

Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.

Mold or Mildew Covered Surfaces: Wash the area with a mildew remover, rinse with water and allow to dry before painting.

Masonry, Brick, Stucco (Popcorn Ceilings) and Plaster: KILZ Stainblocking Ceiling Paint may be used on clean, dry, aged masonry surfaces. New masonry must be allowed to cure (dry) at least 30 days before applying KILZ Stainblocking Ceiling Paint.

Fire Restoration: It is critical to clean smoke damaged surfaces thoroughly before painting. Prime smoke damaged surfaces with an oil-based primer before painting. Primary Recommendation: KILZ COMPLETE®, KILZ ODORLESS® or KILZ ORIGINAL Primers.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP:

- Clean equipment and paint spatters with warm, soapy water.
- If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations.
- Do not dispose of this product down a drain.
- Please consider donating any unused product.
- For recycling or disposal information, contact your local household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2014			
SCAQMD	YES	MPI	NO
CARB	YES	MPI X-GREEN	NO
OTC	YES	GREENGUARD	NO
LADCO	YES	GREEN SEAL™	NO
AIM	YES	CHPS	NO
LEED®	YES*	NAHB/ICC NGBS	NO

* Product may help projects qualify for LEED credits. Please see www.usgbc.org/LEED for additional details.

CAUTIONS/LIMITATIONS:

- Eye protection is recommended.
- Only apply if surface, air and product temperatures are between 50° – 90°F (10° – 32°C).
- Stir thoroughly before and occasionally during use.
- Stainblocking: Multiple coats may be required for complete stainblocking and hide.

GENERAL INFORMATION:

Warning! Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

FIRST AID: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a technical service representative, call 1-866-275-5459 (1-866-ASK-KILZ) • www.kilz.com

Revised 6/2015