



## OVER ARMOR® TEXTURED SOLID COLOR COATING



### PRODUCT INFORMATION

OVER ARMOR® Textured Solid Color Coating is an innovative, waterproofing solid color coating that will bring your old, weathered wood or concrete back to life. The advanced 100% acrylic resin creates a durable coating on your tired deck, rejuvenating its look. Over Armor Textured Solid Color Coating is designed to conceal splinters & cracks up to 1/4" and creates a textured, slip-resistant finish. It is available in a selection in a selection of popular wood colors.

### RECOMMENDED USES:

Recommended for properly prepared exterior weathered or cracked horizontal and vertical surfaces such as:

- Wood
- Composite
- Concrete

Do not use on drivable surfaces such as garage floors and driveways.

### PRODUCT SPECIFICATIONS:

**Tint Bases/Max Tint Load:**

No. L3925 116 oz./14 oz.

**Resin Type:** 100% Acrylic

**Weight per Gallon:** 11.5 lbs

**% Solids by Volume:** 51%

**% Solids by Weight:** 65%

**VOC:** <50 g/L

**Flash Point:** N/A

**Viscosity:** 95-115 KU (Paste Paddle)

**Recommended Film Thickness:**

Wet: 21 mils Dry: 11 mils @ 75 Sq. Ft./Gal.  
per 2 coats (5.5 mils Dry per coat)

**Coverage:** 75 Sq. Ft./Gal. 2 coats required.

### APPLICATION:

**Brush:** Nylon/polyester brush

**Roller:** 1/4" - 1/2" nap

**DO NOT USE WITH AIRLESS SPRAYER**

**Dry Time:** @ 77° & 50% RH

**To Recoat:** 4-6 hours

**Light Foot Traffic:** 24-48 hours

**Full Cure:** 72 hours

- For nail holes and cracks up to 1/4", completely fill in with Over Armor coating using a nylon/polyester brush and allow to dry prior to rolling. Deep nail holes and cracks may require additional filling.
- Use pressure while rolling and apply generously.
- Avoid painting if humidity is expected to be greater than 80%
- 2 coats required

### SURFACE PREPARATION:

**The following steps and products are required:**

(Proper surface preparation is required.)

**Exterior Wood Surfaces:** Replace rotting or unstable boards and remove loose splinters. For exterior old coatings or to remove loose wood fibers, use a product such as KILZ Wood Stain & Finish Stripper followed by KILZ Wood Cleaner & Brightener to neutralize the wood. When KILZ Wood Stain & Finish Stripper is not needed, a product such as KILZ Wood Cleaner & Brightener MUST be used to remove mill glaze and clean the exterior wood surface. After using either KILZ Wood Stain & Finish Stripper or KILZ Wood Cleaner & Brightener, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface. Allow the area to dry at least 24 hours before coating. Lightly sand to remove remaining wood fibers/fuzz.

**Concrete Surfaces:** Avoid areas that are structurally weak or subject to hydrostatic pressure up to 8 psi. Allow new surfaces to cure for 30 days. Use a product such as KILZ Concrete & Masonry Paint Stripper to strip peeling coating. Use a product such as KILZ Concrete & Masonry Cleaner & Etcher to clean and etch uncoated concrete or KILZ Concrete & Masonry Degreaser & Cleaner on sound, coated surfaces prior to coating. See [www.kilz.com](http://www.kilz.com) for additional product information.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### CLEAN UP:

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2014			
SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	FLAME SPREAD/CLASS A	YES

### CAUTIONS/LIMITATIONS:

- Protect from freezing
- Do not use without the addition of tinting colorants
- Do not use if rain is expected within 24 hours
- DO NOT THIN PRODUCT
- Avoid applying paint in direct sunlight or hot surfaces
- Test product for color on a small hidden area before proceeding
- Painted surfaces may become slippery when wet
- Shelf life under normal conditions is 2 years (unopened containers)
- Do not use on drivable surfaces such as garage floors and driveways.
- Temperature Range: 50-90°F (10-32°C)

### GENERAL INFORMATION:



**Warning!** Causes eye and skin irritation. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**First aid: If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.